

# Multi9 - shunt trip release with OC - MX + OF - 110/415 V AC - 110/130 V DC

M9A26946

Product availability: Stock - Normally stocked in distribution facility

### Main

range of product	Multi9	
Product or Component Type	Shunt trip release with OC contact	
Device short name	MX + OF	
Signal contacts composition	1 C/O	
Line Rated Current	3 A at 415 V, AC 6 A at <= 240 V, AC	
[Uc] control circuit voltage	110415 V AC 50/60 Hz 110130 V DC	
9 mm pitches	2	

## Complementary

Range compatibility	Multi9 C60BP Multi9 C60BPR Multi9 C60SP Multi9 GFP Multi9 C60H-DC	
Local signalling	Action indicator	
Mounting Mode	Fixed	
Mounting Support	DIN rail	
Comb busbar and distribution block compatibility	Top YES	
Height	3.2 in (82.5 mm)	
Width	0.7 in (18 mm)	
Depth	2.7 in (68 mm)	
Net Weight	0.143 lb(US) (0.065 kg)	
Connections - terminals	Clamp terminal bottom) - 1 0.004 in² (2.5 mm²) AWG 14) - rigid Clamp terminal bottom) - 2 0.002 in² (1.5 mm²) AWG 16) - rigid	
Wire stripping length	0.4 in (9 mm) for bottom connection	
Tightening torque	8.9 lbf.in (1 N.m) bottom	

## **Environment**

Standards	EN/IEC 60947-2
Product Certifications	ccc
	UL
	PCT
	UR
Pollution dograp	
Pollution degree	3

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient Air Temperature for Operation	-13122 °F (-2550 °C)
Ambient Air Temperature for Storage	-40185 °F (-4085 °C)

# Ordering and shipping details

Category	US10DE200948
Discount Schedule	0DE2
GTIN	3606480639074
Returnability	Yes
Country of origin	ES

# **Packing Units**

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.2 in (3 cm)
Package 1 Width	3.07 in (7.8 cm)
Package 1 Length	3.7 in (9.4 cm)
Package weight(Lbs)	2.5 oz (70.9 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	3.3 in (8.5 cm)
Package 2 Width	3.9 in (10 cm)
Package 2 Length	10.4 in (26.5 cm)
Package 2 Weight	22.3 oz (633 g)
Unit Type of Package 3	S03
Number of Units in Package 3	32
Package 3 Height	11.8 in (30 cm)
Package 3 Width	11.8 in (30 cm)
Package 3 Length	15.7 in (40 cm)
Package 3 Weight	6.464 lb(US) (2.932 kg)



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

#### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.