

# Product datasheet

Specifications



## M9 CT Contactor with Manual Control - 63A - 4P - 4NO - U<sub>c</sub> 220...240V AC 50Hz

M9C21864

### Main

Range	M9
Product name	M9 CT
Product or component type	Contacteur
Device short name	CT
Device application	Motor - heating - lighting
Poles description	4P
[I <sub>e</sub> ] rated operational current	63A AC-7a 20A AC-7b
Pole contact composition	4 NO
Network type	AC
Control type	Remote & Manual control
[U <sub>c</sub> ] control circuit voltage	220...240V AC 50Hz
Standards	IEC/EN 61095 IEC/EN 60947-4-1
Product certifications	CE

### Complementary

Network frequency	50 Hz
[U <sub>e</sub> ] rated operational voltage	400V AC 50Hz
Heat dissipation	2.1 W at 400V AC
[U <sub>i</sub> ] rated insulation voltage	500 V AC 50 Hz conforming to EN/IEC 60947-2
[U <sub>imp</sub> ] rated impulse withstand voltage	2.5 kV
Control signal type	Maintained
Switching frequency	6 switching operations/minute
Local signalling	Action indicator
Hold-in power consumption in VA	7 VA
Inrush power in VA	48 VA

# Product datasheet

## Specifications

Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	6
Height	85 mm
Width	54 mm
Depth	73 mm
Product weight	340 g
Color	Grey
Mechanical durability	1,000,000 cycles
Electrical durability	100,000 cycles IEC/EN 61095 63A 50Hz AC-7a 30,000 cycles IEC/EN 61095 20A 50Hz AC-7b, AC-7c 100,000 cycles IEC/EN 60947-4-1 50 Hz AC-1 30,000 cycles IEC/EN 60947-4-1 50 Hz AC-3, AC-5a, AC-5b
Connections - terminals	<b>Control circuit:</b> <ul style="list-style-type: none"><li>• Tunnel type terminals 1 to 16 mm<sup>2</sup> copper cable - rigid, flexible, flexible with ferrule</li><li>• Tunnel type terminals two 1.5 mm<sup>2</sup> copper cables - rigid, flexible, flexible with ferrule</li></ul> <b>Power circuit:</b> <ul style="list-style-type: none"><li>• Tunnel type terminals 6 to 25 mm<sup>2</sup> copper cable - rigid</li><li>• Tunnel type terminals 6 to 16 mm<sup>2</sup> copper cable - flexible or with ferrule</li></ul>
Wire stripping length	<b>Control circuit:</b> 10 mm <b>Power circuit:</b> 14 mm
Tightening torque	<b>Control circuit:</b> 0.8 N.m <b>Power circuit:</b> 3.5 N.m
Product compatibility	ACTs
Compatibility code	CT
Market segment	Small commercial Residential

## Environment

Noise level	30 dB
IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Pollution degree	2 conforming to IEC/EN 60947-2
Electromagnetic compatibility	8/20 $\mu$ s impulse withstand, 250 A
Tropicalization	2 conforming to IEC/EN 60947-4-1 2 conforming to IEC/EN 61095
Relative humidity	95% at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-40...70 °C

# Product datasheet

Specifications

## Order and shipping

---

Unit type of package 1	SA6
Number of units in package 1	1
Package 1 height	8.5 cm
Package 1 width	5.6 cm
Package 1 length	9.5 cm
Package 1 weight	365 g
Unit type of package 2	S02b
Number of units in package 2	40
Package 2 height	20 cm
Package 2 width	32 cm
Package 2 length	40 cm
Package 2 weight	15.6 kg

## Contractual warranty

---

24 months