

# Product datasheet

Specifications



24340-SE

## M9 - C60N - MCB - 2P - 32A - C Curve

M9F11232

### Main

|                           |                                                                                                                                                                                                                                        |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                     | M9                                                                                                                                                                                                                                     |
| Product name              | C60                                                                                                                                                                                                                                    |
| Product or component type | Miniature circuit-breaker                                                                                                                                                                                                              |
| Device short name         | C60N                                                                                                                                                                                                                                   |
| Device application        | Distribution                                                                                                                                                                                                                           |
| Poles description         | 2P                                                                                                                                                                                                                                     |
| Number of protected poles | 2                                                                                                                                                                                                                                      |
| [In] rated current        | 32A at 30°C conforming to IEC 60898-1                                                                                                                                                                                                  |
| Network type              | AC<br>DC                                                                                                                                                                                                                               |
| Trip unit technology      | Thermal-magnetic                                                                                                                                                                                                                       |
| Curve code                | C                                                                                                                                                                                                                                      |
| Breaking capacity         | 20 kA Icu at $\leq 125$ V DC conforming to IEC/EN 60947-2<br>20 kA Icu at 230...240 V AC conforming to IEC/EN 60947-2<br>10 kA Icu at 400...415 V AC conforming to IEC/EN 60947-2<br>6 kA Icu at 440 V AC conforming to IEC/EN 60947-2 |
| Utilization category      | Category A conforming to EN/IEC 60947-2                                                                                                                                                                                                |
| Suitability for isolation | Yes. Conforming to IEC 60947-2                                                                                                                                                                                                         |
| Standards                 | IEC 60947-2<br>IEC 60898-1                                                                                                                                                                                                             |

### Complementary

|                                |                                                                                                           |
|--------------------------------|-----------------------------------------------------------------------------------------------------------|
| Network frequency              | 50/60 Hz                                                                                                  |
| [Ue] rated operational voltage | $\leq 125$ V DC<br>230...240 V AC 50/60 Hz<br>400 V AC 50/60 Hz<br>415 V AC 50/60 Hz<br>440 V AC 50/60 Hz |
| Limitation class               | 3 conforming to IEC 60898                                                                                 |

# Product datasheet

## Specifications

|                                        |                                                                                       |             |                |
|----------------------------------------|---------------------------------------------------------------------------------------|-------------|----------------|
| [Ui] rated insulation voltage          | 500 V AC 50/60 Hz conforming to IEC/EN 60947-2                                        |             |                |
| Magnetic tripping limit                | IEC 60898-1:                                                                          | 5...10 x In |                |
|                                        | IEC 60947-2:                                                                          | in a.c.     | 8 x In (±20%)  |
|                                        |                                                                                       | in d.c.     | 12 x In (±20%) |
| [Ics] rated service breaking capacity  | 20 kA 100% of Icu at ≤ 125 V DC conforming to IEC/EN 60947-2                          |             |                |
|                                        | 15 kA 75% of Icu at 230...240 V AC conforming to IEC/EN 60947-2                       |             |                |
|                                        | 7.5 kA 75% of Icu at 400...415 V AC conforming to IEC/EN 60947-2                      |             |                |
|                                        | 4.5 kA 75% of Icu at 440 V AC conforming to IEC/EN 60947-2                            |             |                |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC/EN 60947-2                                                     |             |                |
| Contact position indicator             | Yes                                                                                   |             |                |
| Control type                           | Toggle                                                                                |             |                |
| Local signalling                       | ON/OFF indication                                                                     |             |                |
| Mounting mode                          | Clip-on                                                                               |             |                |
| Mounting support                       | 35 mm symmetrical DIN rail                                                            |             |                |
| 9 mm pitches                           | 4                                                                                     |             |                |
| Height                                 | 81 mm                                                                                 |             |                |
| Width                                  | 36 mm                                                                                 |             |                |
| Depth                                  | 72 mm                                                                                 |             |                |
| Product weight                         | 240 gr                                                                                |             |                |
| Color                                  | Grey                                                                                  |             |                |
| Mechanical durability                  | 20,000 cycles                                                                         |             |                |
| Electrical durability                  | 10,000 cycles                                                                         |             |                |
| Provision for padlocking               | Padlockable                                                                           |             |                |
| Connections - terminals                | Tunnel type terminal (top or bottom) 1.5...16 mm <sup>2</sup> - rigid                 |             |                |
|                                        | Tunnel type terminal (top or bottom) 1.5...16 mm <sup>2</sup> - flexible              |             |                |
|                                        | Tunnel type terminal (top or bottom) 1.5...16 mm <sup>2</sup> - flexible with ferrule |             |                |
| Wire stripping length                  | 14 mm top or bottom connection                                                        |             |                |
| Tightening torque                      | 3.5 N.m top or bottom                                                                 |             |                |
| Earth-leakage protection               | Separate add-on block                                                                 |             |                |

## Environment

|                                       |                                                  |
|---------------------------------------|--------------------------------------------------|
| Heat dissipation                      | 7.0 W at 415 V - 32 A                            |
| IP degree of protection               | IP20 conforming to IEC 60529                     |
|                                       | IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution degree                      | 3 conforming to IEC/EN 60947-2                   |
| Overvoltage category                  | IV                                               |
| Tropicalization                       | 2 conforming to IEC 60068-1                      |
| Relative humidity                     | 95% at 55 °C                                     |
| Ambient air temperature for operation | -30...70 °C                                      |
| Ambient air temperature for storage   | -40...80 °C                                      |

# Product datasheet

Specifications

## Ordering and shipping details

|      |               |
|------|---------------|
| GTIN | 6267377143400 |
|------|---------------|

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit type of package 1       | BB1     |
| Number of units in package 1 | 6       |
| Package 1 height             | 7.8 cm  |
| Package 1 width              | 8.7 cm  |
| Package 1 length             | 22 cm   |
| Package 1 weight             | 1.5 kg  |
| Unit type of package 2       | GB1     |
| Number of units in package 2 | 60      |
| Package 2 height             | 31.5 cm |
| Package 2 width              | 26.5 cm |
| Package 2 length             | 28 cm   |
| Package 2 weight             | 16.5 kg |

## Contractual warranty

|           |          |
|-----------|----------|
| Guarantee | Lifetime |
|-----------|----------|