

Multi9 - undervoltage release - MN - 48 V AC - 48 V DC

M9A26961

Product availability: Stock - Normally stocked in distribution facility

Main

range of product	Multi9
Product or Component Type	Undervoltage release
Device short name	MN
[Uc] control circuit voltage	48 V AC 50/60 Hz 48 V DC
Control Type	Standard
9 mm pitches	2

Complementary

Range compatibility	Multi9 C60BP Multi9 C60BPR Multi9 C60SP Multi9 GFP Multi9 C60H-DC	
Local signalling	Action indicator	
Mounting Mode	Fixed	
Mounting Support	DIN rail	
Comb busbar and distribution block compatibility	Top YES	
Height	3.2 in (82.5 mm)	
Width	0.7 in (18 mm)	
Depth	2.7 in (68 mm)	
Net Weight	0.146 lb(US) (0.066 kg)	
Connections - terminals	Clamp terminal bottom) - 1 0.004 in² (2.5 mm²) AWG 14) - rigid Clamp terminal bottom) - 2 0.002 in² (1.5 mm²) AWG 16) - rigid	
Wire stripping length	0.4 in (9 mm) for bottom connection	
Tightening torque	8.9 lbf.in (1 N.m) bottom	

Environment

Standards	EN/IEC 60947-2	
Product Certifications	PCT UL UR	
Pollution degree	3	
Ambient air temperature for operation	-13122 °F (-2550 °C)	
Ambient Air Temperature for Storage	-40185 °F (-4085 °C)	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

Category	US10DE200948
Discount Schedule	0DE2
GTIN	3606480639128
Returnability	Yes
Country of origin	BE

Packing Units

Unit Type of Package 1	PCE	
Nbr. of units in pkg.	1	
Package 1 Height	1.142 in (2.900 cm)	
Package 1 Width	3.150 in (8.000 cm)	
Package 1 Length	3.701 in (9.400 cm)	
Package weight(Lbs)	2.575 oz (73.000 g)	
Unit Type of Package 2	BB1	
Number of Units in Package 2	8	
Package 2 Height	3.425 in (8.700 cm)	
Package 2 Width	3.937 in (10.000 cm)	
Package 2 Length	10.433 in (26.500 cm)	
Package 2 Weight	22.857 oz (648.000 g)	
Unit Type of Package 3	S03	
Number of Units in Package 3	72	
Package 3 Height	11.811 in (30.000 cm)	
Package 3 Width	11.811 in (30.000 cm)	
Package 3 Length	15.748 in (40.000 cm)	
Package 3 Weight	13.918 lb(US) (6.313 kg)	



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

⊗ Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	De0ee70b-a441-4aab-aaa6-a931298bfc8d
REACh Regulation	REACh Declaration
Silicon free	No

Use Again

○ Repack and remanufacture		
Take-back	No	
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	